



Panther PRO Gas Leak Detector

0186



Servicies

After sale servicies

Ordinary and extraordinary maintenance, installation, staff training, spare parts, calibration and calibration for measuring instruments.

The prices could be not always up to date and they don't take into account any promotional sale on the e-commerce.



Product description

With over thirty years of solid experience in leak detection, the Panther emerges as the successful evolution of the renowned GasCheck series. Created for the precise identification of gas leaks, the Panther stands out for its ergonomics, making it natural to handle. Its use is intuitive: drag it at a speed of approximately 25 mm per second along the area to be tested. When you detect a leak, take a slower step until you locate it. Once identified, place the tool on the leak and wait for the measurement to stabilize. The Panther, with its effectiveness and ease of use, establishes itself as an indispensable companion for accurate and reliable control of gas leaks.



General Features

Dimensions	320mm x 80mm x 55mm (approssimativamente)	Weight	447g (approximately)
Range	2 cc/min	Battery life	Rechargeable lithium ion battery
Battery life	Duration: 20 hours	Temperature	Operation: from 0°C to 50°C
Sensitivity	• Helium: 5×10-6 • Hydrogen: 3.8 x10-6	Calibration	At 50% relative humidity (room temperature) • 5000 ppm Helium (± 5%) • Leakage: 0.0005 cc/sec (± 5%)
Allarme	Greater than 90 dB @ 10cm	Connettività	Bluetooth
Detector	Micro-Thermal Conductivity Detector (MTCD)	Probe	20cm flexible hose
Humidity	0-99% R.H	Humidity	0-99% R.H