

ComastriDistribution

Phone: +390513510702

Mail: info@comastridistribution.com



Go to product



Dynamometer PCE-DFG 5K X-ICA

0217









Servicies

After sale servicies

Ordinary and extraordinary maintenance, installation, staff training, spare parts, calibration and calibration for measuring instruments.



ComastriDistribution

Phone: +390513510702

Mail: info@comastridistribution.com



Go to product

Product description

Five-star precision and versatility define the PCE-DFG N 5K-ICA dynamometer, designed for high-resolution tension and compression testing. This tool excels at handling force-distance curves, breaking force, and other critical measurements frequently encountered in laboratories.

The PCE-DFG N 5K-ICA comes complete with an external load cell offering a measurement capacity of up to 5,000 Newtons, with the flexibility to customize load cells with M12 threaded pins or hooks to adapt to various devices.

Its USB interface facilitates data transfer to the PC, enabling the creation of measurement protocols, data storage, and result exportation. Additionally, the dynamometer features an LCD graphical display that presents values in both numerical and graphical formats, simplifying result interpretation.

The included ISO certification ensures measurement quality, while its robustness with IP54 protection makes it suitable for industrial use, even in adverse environmental conditions.

A standout feature of the PCE-DFG N 5K-ICA is its ability to easily interchange load cells, allowing for measurement customization based on specific needs. With a rapid response time, included software, and the capability to store up to 100 sets of measurements, this instrument offers a wide range of functionalities.

In summary, the PCE-DFG N 5K-ICA dynamometer stands out for its precision, versatility, and ease of use, providing a comprehensive solution for your measurement needs in both laboratory and industrial settings.



ComastriDistribution

Phone: +390513510702

Mail: info@comastridistribution.com



Go to product

General Features

| Dimensions | 200mm x 97mm x 42 mm | Dimensions | 200mm x 97mm x 42 mm |
|--------------------|---|--------------------|----------------------|
| Weight | 540 g | Weight | 540 g |
| Resolution | 1 N | Resolution | 1 N |
| Battery life | About 10 hours | Battery life | Circa 10 ore |
| Range | 0 5.000 N | Range | 0 5.000 N |
| Power | 1 x NiMh battery, 6V / 1600 mAh | Power | 12 V / 1 A |
| Power | 12 V / 1 A | Power | 1 x Batteria NiMh |
| Power | 6V / 1600 mAh | Measurements Units | N, kg, lb, KPa |
| Measurements Units | N | Measurements Units | kg |
| Measurements Units | lb | Measurements Units | КРа |
| Memory | 100 measurement series, with 8,000 values per | Memory | 100 serie di misura |
| | series | | |
| Memory | con 8.000 valori per serie | Precision | ±0,1% F.S. |
| Precision | ±0 | Precision | ±0 |