



## ***Sound level meter and acoustic calibrator PCE-430-SC 09-ICA***

0227



## ***Servicies***

### **After sale servicies**

Ordinary and extraordinary maintenance, installation, staff training, spare parts, calibration and calibration for measuring instruments.



## Product description



## General Features

<b>Battery life</b>	Minimum 10 hours	<b>Range</b>	22 ... 136 db(A)
<b>Allarme</b>	Adjustable	<b>Power</b>	4 x 1.5V AA batteries; 12V/1A power supply; 5V/1A USB
<b>Sampling</b>	Standard: 48 kHz Mode LN: 20 ms	<b>Memory</b>	4GB micro SD card
<b>Functions</b>	LXY(SPL), LXeq, LXYSD, LXSEL, LXE, LXYmax, LXYmin, LXPeak, LXN; X - Ponderazione frequenza: A, B, C, Z; Y - Ponderazione temporale: F, S, I; N - Statistica in % : 1 ... 99%	<b>Precision</b>	1st Class
<b>Frequency range</b>	3 Hz ... 20 kHz	<b>Standards</b>	GB/T3785.1-2010; GB/T3785.2-2010; IEC60651:1979; IEC60804:2000; IEC61672-1:2013; ANSI S1.4-1983; ANSI S1.43-1997
<b>Standards</b>	GB/T3785.1-2010; GB/T3785.2-2010; IEC60651:1979; IEC60804:2000; IEC61672-1:2013; ANSI S1.4-1983; ANSI S1.43-1997		