



Sound level meter PCE-432 and acoustic calibrator PCE-SC 09

0232



Servicies

After sale services

Ordinary and extraordinary maintenance, installation, staff training, spare parts, calibration and calibration for measuring instruments.

The prices could be not always up to date and they don't take into account any promotional sale on the e-commerce.



Product description

Portable Sound Level Meter with Built-In GPS PCE-432:

A first-class instrument designed for precise noise measurement and frequency analysis. This sound level meter includes an integrated GPS receiver for accurate geospatial data recording. It also comes with ISO certification for regulatory compliance. Its measurement range spans from 22 to 136 dB(A) with a frequency range of 3 Hz to 20 kHz, making it ideal for workplace noise assessment and hearing protection.

The PCE-432 complies with relevant standards, including EN/IEC 61672, ANSI S1.4-1983, ANSI S1.43-1997, and EN/IEC61260. It features a backlit display for real-time visualization of sound pressure levels, enhancing data readability.

This professional tool is equipped with a built-in data logger that stores measurements on a micro SD card, easily exportable and analyzable via USB connection to a computer using dedicated software.

The PCE-432 sound level meter finds applications in workplace noise assessment, environmental noise monitoring, evaluation of noise exposure, and implementation of hearing protection measures. It includes an Impulse function for recording brief sound events and supports customizable measurement profiles, specific limits, and various time and frequency weightings (A, C, Z) for adaptability. In summary, the Portable Sound Level Meter PCE-432 represents a comprehensive solution for noise measurement, combining precision, advanced functionality, and ease of use.

Portable Acoustic Calibrator PCE-SC 09:

A battery-powered sound source for quick and direct calibration of sound level meters and other systems. Adapters allow for connecting and testing microphones of various sizes.

This acoustic calibrator operates at a calibration frequency of 1000 Hz, serving as a reference for international standard weighting curves (A, B, C, or D). The calibration pressure of the acoustic calibrator is 94 ± 0.3 dB (1 Pa) and 114 ± 0.3 dB (10 Pa), suitable for quality control and calibration of sound level meters. It is easy to use and compatible with various microphone types.



ComastriDistribution
Prodotti e soluzioni per l'industria S.r.l

19/05/2024

ComastriDistribution

Phone: +390513510702

Mail: info@comastridistribution.com



[Go to product](#)

General Features

Range	22 ... 136 db(A)	Allarme	Adjustable
Power	4 x 1.5V AA batteries; 12V/1A power supply; 5V/1A USB	Memory	4GB micro SD card
Functions	LXY(SPL), LXeq, LXYSD, LXSEL, LXE, LXYmax, LXYmin, LXPeak, LXN; X - Frequency Weighting: A, B, C, Z; Y - Time Weighting: F, S, I; N - Statistics in %: 1 ... 99%	Precision	1st Class
Frequency range	3Hz ... 20kHz	Standards	GB/T3785.1-2010; GB/T3785.2-2010; IEC60651:1979; IEC60804:2000; IEC61672-1:2013; ANSI S1.4-1983; ANSI S1.43-1997
Standards	GB/T3785.1-2010; GB/T3785.2-2010; IEC60651:1979; IEC60804:2000; IEC61672-1:2013; ANSI S1.4-1983; ANSI S1.43-1997		

Base price:

VAT excluded
2,071.07 €

VAT included
2,526.70 €

Model ref. 4250348728562

The prices could be not always up to date and they don't take into account any promotional sale on the e-commerce.

comastridistribution.com

Page 3/3