

#### ComastriDistribution

Phone: +390513510702

Mail: info@comastridistribution.com



Go to product



**CTS-P** 0253

# **Servicies**

After sale servicies

Ordinary and extraordinary maintenance, installation, staff training, spare parts, calibration and calibration for measuring instruments.



#### ComastriDistribution

Phone: +390513510702

Mail: info@comastridistribution.com



Go to product

# **Product description**

The CTS, like the CTE, allows testing the seal of industrial packaging such as vials, bottles, flasks, etc. Suitable for production environments, it features a fully pneumatic system capable of creating a vacuum, a compressed air control valve to limit incoming flow, and a needle gauge. This model is available with a vacuum pump system.



## ComastriDistribution

Phone: +390513510702

Mail: info@comastridistribution.com



Go to product

## **General Features**

Temperature	From 0°C to +40°C	Power	Compressed air from 6 to 8 bar connected via an
			8 mm Rislan® tube up to -0.850 bar (not
			supplied). Vacuum pump (Max -920 mbar)
Power	Aria compressa da 6 a 8 bar collegata tramite	Power	850 bar (non fornito). Pompa per vuoto (Max -920
	tubo Rislan® da 8 mm fino a -0		mbar)
Capacity	-950 mBar	Standards	ASTM D4991, ASTM D5094, ASTM D4169, EN
			14401, DIN 55528 (Parts 1, 2, 3, 4, 5)
Standards	ASTM D4991	Standards	ASTM D5094
Standards	ASTM D4169	Standards	EN 14401
Standards	DIN 55528 (Parts 1	Standards	2
Standards	3	Standards	4
Standards	5)	Vacuum	Vacuum pump supplied
Application	Leak test	Cassa	Transparent PMMA chamber with hinge
Measurement range	From -0.1 to -0.85 Bar (relative pressure) as	Measurement range	Da -0
and accuracy	standard. Accuracy: +/- 2%	and accuracy	
Measurement range	1 a -0	Measurement range	85 Bar (pressione relativa) di serie. Precisione: +/-
and accuracy		and accuracy	2%
Depression reading	Needle vacuum gauge with a resolution of 50	Units	Bar, Psi
	mbar		
Units	Bar	Units	Psi
Units	Psi		