



CTS-P

0253

Servicies

After sale servicies

Ordinary and extraordinary maintenance, installation, staff training, spare parts, calibration and calibration for measuring instruments.



Product description

The CTS, like the CTE, allows testing the seal of industrial packaging such as vials, bottles, flasks, etc. Suitable for production environments, it features a fully pneumatic system capable of creating a vacuum, a compressed air control valve to limit incoming flow, and a needle gauge. This model is available with a vacuum pump system.



Comastri Distribution
Prodotti e soluzioni per l'industria S.r.l

17/09/2025

ComastriDistribution

Phone: +390513510702

Mail: info@comastridistribution.com



[Go to product](#)

General Features

Temperature	From 0°C to +40°C	Power	Compressed air from 6 to 8 bar connected via an 8 mm Rislan® tube up to -0.850 bar (not supplied). Vacuum pump (Max -920 mbar)
Power	Aria compressa da 6 a 8 bar collegata tramite tubo Rislan® da 8 mm fino a -0	Power	850 bar (non fornito). Pompa per vuoto (Max -920 mbar)
Capacity	-950 mBar	Standards	ASTM D4991, ASTM D5094, ASTM D4169, EN 14401, DIN 55528 (Parts 1, 2, 3, 4, 5)
Standards	ASTM D4991	Standards	ASTM D5094
Standards	ASTM D4169	Standards	EN 14401
Standards	DIN 55528 (Parts 1	Standards	2
Standards	3	Standards	4
Standards	5)	Vacuum	Vacuum pump supplied
Application	Leak test	Cassa	Transparent PMMA chamber with hinge
Measurement range and accuracy	From -0.1 to -0.85 Bar (relative pressure) as standard. Accuracy: +/- 2%	Measurement range and accuracy	Da -0
Measurement range and accuracy	1 a -0	Measurement range and accuracy	85 Bar (pressione relativa) di serie. Precisione: +/- 2%
Depression reading	Needle vacuum gauge with a resolution of 50 mbar	Units	Bar, Psi
Units	Bar	Units	Psi
Units	Psi		

The prices could be not always up to date and they don't take into account any promotional sale on the e-commerce.