



Panther

0270



Servicies

After sale services

Ordinary and extraordinary maintenance, installation, staff training, spare parts, calibration and calibration for measuring instruments.



Comastri Distribution
Prodotti e soluzioni per l'industria S.r.l

14/12/2025

ComastriDistribution

Phone: +390513510702

Mail: info@comastridistribution.com



[Go to product](#)

Product description

The prices could be not always up to date and they don't take into account any promotional sale on the e-commerce.

comastridistribution.com

Page 2/3



General Features

Dimensions	320 x 80 x 55 mm (approx.)	Weight	447 g (approx.)
Range	2 cc/min	Response time	T90: 1 second
Battery life	Rechargeable Li-ion battery	Temperature	From 0°C to 50°C
Humidity	0-99% R.H	Detector	Micro thermal conductivity detector (MTCD)
Battery life	20 hours	Audible Alarm	90 dBa at 10 cm
Factory calibration	At 50 % relative humidity, room temperature: 5000 ppm helium ($\pm 5\%$) Leak: 0.0005 cc/s ($\pm 5\%$)	Data logging	10 days continuous
Sensitivity (cc/s)	Sensitivity (cc/s) Helium: 5×10^{-6} Hydrogen: 3.8×10^{-6}	Sensitivity (cc/s)	Sensitivity (cc/s) Helium: 5×10^{-6} Hydrogen: 3.8×10^{-6}