01/07/2025



ComastriDistribution

Phone: +390513510702 Mail: info@comastridistribution.com



0271

Go to product





After sale servicies

Ordinary and extraordinary maintenance, installation, staff training, spare parts, calibration and calibration for measuring instruments.

The prices could be not always up to date and they don't take into account any promotional sale on the e-commerce.

01/07/2025



ComastriDistribution

Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

Product description

The prices could be not always up to date and they don't take into account any promotional sale on the e-commerce.



ComastriDistribution

Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

General Features

Dimensions	320 x 80 x 55 mm (approx.)	Weight	447 g (approx.)
Range	2 cc/min	Response time	T90: 1 second
Battery life	Rechargeable Li-ion battery	Temperature	From 0°C to 50°C
Humidity	0-99% R.H	Detector	Micro thermal conductivity detector (MTCD)
Battery life	20 hours	Audible Alarm	90 dBa at 10 cm
Factory calibration	At 50 % relative humidity, room temperature: 5000	Data logging	10 days continuous
	ppm helium (± 5%) Leak: 0.0005 cc/s (± 5%)		
Sensitivity (cc/s)	Sensitivity (cc/s) Helium: 5 x 10-6 Hydrogen: 3.8 x	Sensitivity (cc/s)	Sensitivity (cc/s) Helium: 5 x 10-6 Hydrogen: 3.8 x
	10-6		10-6

The prices could be not always up to date and they don't take into account any promotional sale on the e-commerce.