



GasCheck G - Portable leak detector

0037



Servicies

After sale servicies

Ordinary and extraordinary maintenance, installation, staff training, spare parts, calibration and calibration for measuring instruments.

Rental

If you need this product occasionally, renting may be the most convenient solution for your business.

The prices could be not always up to date and they don't take into account any promotional sale on the e-commerce.



Product description

GasCheck G is a device designed for detecting gas leaks, equipped with an advanced micro-sensor suitable for detecting almost all types of gases. It provides accurate and reliable readings, signaling leaks through an LCD display, an LED indicator, and auditory alarms. The interface is intuitive, and the device is user-friendly, featuring a large backlit LCD screen. It is especially sensitive to gases such as ammonia and hydrogen. Users have the flexibility to choose from different reading modes, and the sensitivity can be expanded.

GasCheck G is available in two versions, G2 and G3, which can be easily upgraded without sending them back to the manufacturer.

Feature

G2

G3

Rapid detection of gas leaks

-
-

Measures gas leaks (single gas)

-

Measures gas leaks (up to 20 gases)

-

Audible sounder

-
-

Flashing back-lit display

-
-

Peak hold readings

-
-

Factory or custom calibration available

The prices could be not always up to date and they don't take into account any promotional sale on the e-commerce.



-
-

Data logging (store up to 10 readings)

-

Readings displayed in cc/sec, g/yr, ppm or mg/m3

-

Selectable battery type

-

Upgradeable

-

What's included

GasCheck instrument

Battery holder

Long probe assembly

Drilled box spanner

Standard universal case

Printed quick start guide (we recommend downloading the Instrument Manual.)



General Features

Dimensions	H:390 mm L:60 mm P:49mm	Weight	
Response time	T90 < 1 second	Accuracy	± 5% + 1 digit
Battery life	40 hours life	Data logging	10 datapoint (only in the G3 version)
Flow rate	2 cc/min	Temperature	-20 to 60 °C
Sensitivity	He1x10e-5, CH4 5x10e-5, R125x10e-5, Ar1x10e-4	Sensitivity	He1x10e-5, CH4 5x10e-5, R125x10e-5, Ar1x10e-4

Models and prices

Model ref.	Model	Price VAT escl.
GG2SAXXS-X	G2 (Helium cc/sec)	2,982.20 €
GG2SAXXS-X	G2 (Helium PPM)	2,982.20 €
GG3SAXXS-X	G3	3,354.00 €