

Phone: +390513510702

Mail: info@comastridistribution.com



Go to product



T4 - Portable multigas detector

0054

# **Servicies**

After sale servicies

Ordinary and extraordinary maintenance, installation, staff training, spare parts, calibration and calibration for measuring instruments.



Phone: +390513510702

Mail: info@comastridistribution.com



Go to product

## **Product description**

Draduat variants and antions

The T4 is a portable multi-gas detector with advanced safety features and a rugged, intuitive design, ideal for harsh environments. It offers protection against key gas-related hazards including CO, H2S, flammable gases, and oxygen deficiency. With an 18-hour battery life and a backlit display, it's designed for extended use. An exclusive feature, the TWA Restart, accurately calculates gas exposure over an entire shift. Approved for high safety standards like Zone 1 ATEX, the device includes auditory, visual, and vibration alarms. Easy to operate with a single large button, the T4 is drop and water-resistant, ensuring reliability under any conditions.

Product variants and options
2 gas - Flammable
2 gas - CO
3 gas - H2S
3 gas - CO
3 gas - CO (H2 immune)
4 gas
4 gas - CO (H2 immune)
Oxygen (O2)
X
x x
X X X
X X X
X X X X
X X X X X
X X X X
X X X X X
X X X X X X
X X X X X X X Flammable
X X X X X X X X X X X X X X X X X X X
X X X X X X X X X X X X X X X X X X X
X X X X X X X X X X X X X X X X X X X

The prices could be not always up to date and they don't take into account any promotional sale on the e-commerce.

Hydrogen sulfide (H2S)



Phone: +390513510702

Mail: info@comastridistribution.com



Go to product

X	
X	
X	
Carbon monoxide (CO)	
X	
X	
X	
Carbon monoxide (H2 immune)	
X	
X	
^	
Gases and ranges	
Range	
Resolution	
Ossigeno (O2)	
0-30% vol.	
0,1% vol.	
Infiammabile	
0-100% LEL	
1% LEL	
Acido solfidrico (H2S)	
0-100 ppm	
1 ppm	
Monossido di carbonio (CO)	
0-1000 ppm	
1 ppm	

Contact us for information about other possible combinations of gas sensors!



Phone: +390513510702

Mail: info @ comastridistribution.com



Go to product

## **General Features**

Dimensions	H:135 mm L:80 mm P:35 mm	Weight	282 g
Battery life	18 hour typical runtime, 5.5 hour recharge	Data logging	130 hours of data at 10s intervals, max 3,500
Temperature	From –20°C to 55°C (from -4°F to 131°F)	Approvals	ATEX, IECEx, UL, INMETRO, MED
Allarme	95dB, vibration integrated, bright red & blue LED's	Classificazione IP	IP65 e IP67
Classificazione IP	IP65 e IP67		

# **Models and prices**

Model ref. Gas Price VAT escl.

IONCWT4-HOCA-IT-CRD T4 4 **G/g/S**s - O2 0-25%, CO, CH4 LEL, H2S

642.00 €