



T4 - Portable multigas detector

0054

Servicies

After sale servicies

Ordinary and extraordinary maintenance, installation, staff training, spare parts, calibration and calibration for measuring instruments.



Product description

The T4 is a portable multi-gas detector with advanced safety features and a rugged, intuitive design, ideal for harsh environments. It offers protection against key gas-related hazards including CO, H₂S, flammable gases, and oxygen deficiency. With an 18-hour battery life and a backlit display, it's designed for extended use. An exclusive feature, the TWA Restart, accurately calculates gas exposure over an entire shift. Approved for high safety standards like Zone 1 ATEX, the device includes auditory, visual, and vibration alarms. Easy to operate with a single large button, the T4 is drop and water-resistant, ensuring reliability under any conditions.

Product variants and options

2 gas - Flammable

2 gas - CO

3 gas - H₂S

3 gas - CO

3 gas - CO (H₂ immune)

4 gas

4 gas - CO (H₂ immune)

Oxygen (O₂)

X
X
X
X
X
X
X
X

Flammable

X
X
X
X
X
X

Hydrogen sulfide (H₂S)



X

X

X

Carbon monoxide (CO)

X

X

X

Carbon monoxide (H2 immune)

X

X

Gases and ranges

Range

Resolution

Ossigeno (O2)

0-30% vol.

0,1% vol.

Infiammabile

0-100% LEL

1% LEL

Acido solfidrico (H2S)

0-100 ppm

1 ppm

Monossido di carbonio (CO)

0-1000 ppm

1 ppm

Contact us for information about other possible combinations of gas sensors!



ComastriDistribution
Prodotti e soluzioni per l'industria S.r.l

08/07/2025

ComastriDistribution

Phone: +390513510702

Mail: info@comastridistribution.com



[Go to product](#)

General Features

Dimensions	H:135 mm L:80 mm P:35 mm	Weight	282 g
Battery life	18 hour typical runtime, 5.5 hour recharge	Battery life	Autonomia 18 ore
Battery life	tempo di ricarica 5	Battery life	5 ore
Data logging	130 hours of data at 10s intervals, max 3,500	Data logging	130 ore di dati a intervalli di 10 sec
Data logging	max capacità 3.500 registrazioni	Temperature	From -20°C to 55°C (from -4°F to 131°F)
Approvals	ATEX, IECEX, UL, INMETRO, MED	Approvals	ATEX
Approvals	IECEX	Approvals	UL
Approvals	INMETRO	Approvals	MED
Allarme	95dB, vibration integrated, bright red & blue LED's	Allarme	95 dB
Allarme	vibrazione integrata	Allarme	LED rossi e blu luminosi
Classificazione IP	IP65 e IP67	Classificazione IP	IP65 e IP67

The prices could be not always up to date and they don't take into account any promotional sale on the e-commerce.