



T4 - Portable multigas detector

0054

Servicies

After sale servicies

Ordinary and extraordinary maintenance, installation, staff training, spare parts, calibration and calibration for measuring instruments.



Product description

The T4 is a portable multi-gas detector with advanced safety features and a rugged, intuitive design, ideal for harsh environments. It offers protection against key gas-related hazards including CO, H2S, flammable gases, and oxygen deficiency. With an 18-hour battery life and a backlit display, it's designed for extended use. An exclusive feature, the TWA Restart, accurately calculates gas exposure over an entire shift. Approved for high safety standards like Zone 1 ATEX, the device includes auditory, visual, and vibration alarms. Easy to operate with a single large button, the T4 is drop and water-resistant, ensuring reliability under any conditions.

Product variants and options

2 gas - Flammable

2 gas - CO

3 gas - H2S

3 gas - CO

3 gas - CO (H2 immune)

4 gas

4 gas - CO (H2 immune)

Oxygen (O2)

X
X
X
X
X
X
X
X

Flammable

X
X
X
X
X
X
X

Hydrogen sulfide (H2S)



Comastri Distribution
Prodotti e soluzioni per l'industria S.r.l

09/05/2025

ComastriDistribution

Phone: +390513510702

Mail: info@comastridistribution.com



[Go to product](#)

X

X

X

Carbon monoxide (CO)

X

X

X

Carbon monoxide (H2 immune)

X

X

Gases and ranges

Range

Resolution

Ossigeno (O2)

0-30% vol.

0,1% vol.

Infiammabile

0-100% LEL

1% LEL

Acido solfidrico (H2S)

0-100 ppm

1 ppm

Monossido di carbonio (CO)

0-1000 ppm

1 ppm

Contact us for information about other possible combinations of gas sensors!

The prices could be not always up to date and they don't take into account any promotional sale on the e-commerce.

comastridistribution.com

Page 3/4



ComastriDistribution
Prodotti e soluzioni per l'industria S.r.l

09/05/2025

ComastriDistribution

Phone: +390513510702

Mail: info@comastridistribution.com



[Go to product](#)

General Features

Dimensions	H:135 mm L:80 mm P:35 mm	Weight	282 g
Battery life	18 hour typical runtime, 5.5 hour recharge	Battery life	Autonomia 18 ore
Battery life	tempo di ricarica 5	Battery life	5 ore
Data logging	130 hours of data at 10s intervals, max 3,500	Data logging	130 ore di dati a intervalli di 10 sec
Data logging	max capacità 3.500 registrazioni	Temperature	From -20°C to 55°C (from -4°F to 131°F)
Approvals	ATEX, IECEX, UL, INMETRO, MED	Approvals	ATEX
Approvals	IECEX	Approvals	UL
Approvals	INMETRO	Approvals	MED
Allarme	95dB, vibration integrated, bright red & blue LED's	Allarme	95 dB
Allarme	vibrazione integrata	Allarme	LED rossi e blu luminosi
Classificazione IP	IP65 e IP67	Classificazione IP	IP65 e IP67

The prices could be not always up to date and they don't take into account any promotional sale on the e-commerce.