

ComastriDistribution

Phone: +390513510702 Mail: info@comastridistribution.com



Go to product



Gasman - Single gas portable detector





Servicies

After sale servicies

Ordinary and extraordinary maintenance, installation, staff training, spare parts, calibration and calibration for measuring instruments.

The prices could be not always up to date and they don't take into account any promotional sale on the e-commerce.

0057



Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

Product description

Choose Gasman for reliable, portable gas detection tailored to your needs. This robust, compact monogas monitor is built for the harshest environments, including oil and gas, chemicals, and recycling industries. With an IP65 rating, it ensures high shock and dust/water ingress protection. Featuring a loud 95dB alarm, vivid red/blue visual warnings, and vibration alerts, Gasman keeps you safe. Easy single-button control and backlit LCD display offer clear gas level and alarm status visibility. Weighing just 130g, it's ultra-lightweight yet durable.

Available in flammable, oxygen, and toxic gas versions with both rechargeable and non-rechargeable options. Stay compliant with 30-day pre-calibration warnings and standard event logging. Choose Gasman for dependable gas monitoring in challenging conditions.

GAS

Intervallo

Allarmi tipici

Ammonia (NH3) 0-1000 ppm 25 ppm

Carbon dioxide (CO2) Vol. 0,5% Vol. 0,5%

Carbon monoxide (CO) 0-1.500 ppm 30 ppm

Carbon monoxide (CO)(hydrogen filtered) 0-500 ppm 30 ppm

Chlorine (Cl2) 0-20 ppm 0,3 ppm

Chlorine dioxide (ClO2) 0-1 ppm 0,1 ppm

Ethylene oxide (ETO) 0-10 ppm



Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

3 ppm

Flammable (LEL) 0-100% LEL 20% LEL

Fluorine (F2) 0-1ppm 0,5 ppm

Hydrogen (H2) 0-2.000 ppm N/A

Hydrogen cyanide (HCN) 0-25 ppm 5 ppm

Hydrogen fluoride (HF) 0-10 ppm 1 ppm

Hydrogen sulphide (H2S) 0-250 ppm 5 ppm

Nitrogen dioxide (NO2) 0-20 ppm 1 ppm

Oxygen (O2) Vol. 0-25% Vol. 19%/23%

Ozone (O3) 0-1 ppm 0,1 ppm

Phosphine (PH3) 0-5 ppm 0,1 ppm

Phosgene (COCl2) 0-1 ppm 0,1 ppm



Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

Sulphur dioxide (SO2) 0-20 ppm 1 ppm

Nitrogen oxide (NO) 0-100 ppm 25 ppm

Contact us for information about other possible combinations of gas sensors!



ComastriDistribution

Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

General Features

Dimensions	H:90 mm L:48 mm P:24 mm	Weight	Different based on the model, max 140g
Weight	Variabile a seconda del modello	Weight	max 140g
Response time	Flammable and toxic gas: 20 seconds; oxygen: 10 seconds	Battery life	Rechargeable lithium battery for all gas types (12 hours minimum), non rechargeable lithium battery for toxics and oxygen (up to 2 years)
Battery life	Batterie al litio ricaricabili per tutti i tipi di gas (minimo 12 ore)	Battery life	batterie al litio non ricaricabili per gas tossici e ossigeno (fino a 2 anni)
Data logging	Full timed data logging with adjustable sample rate, set to 1 min. data rate as default. 900 hours storage at 1 min. interval (54,000 logs), 4800 events	Data logging	Registrazione dati a tempo pieno con frequenza di campionamento regolabile
Data logging	velocità dati impostata su 1 min come predefinita. 900 ore di conservazione a 1 min intervallo (54.000 log)	Data logging	4800 eventi
Temperature	-20 to 60 °C	Temperature	Da -20°C a 60 °C
Calibration	Gasman can be routinely calibrated using Portables Pro software	Calibration	Gasman può essere regolarmente calibrato utilizzando il software Portables Pro
Approvals	Toxic or O2: ATEX II 1G Ex ia IIC T4 Ga (-20°C <= Ta $<=$ +65OC) BASEEFA04ATEX0384; IECEx BAS05.0039. Flammable: ATEX II 2G Ex ia d IIC T4 Gb (-20°C $<=$ Ta $<=$ +65OC) BASEEFA04ATEX0383; IECEx BAS05.0038. CSA Class 1 Groups A,B,C,D Division 1	Approvals	В
Approvals	Toxic or O2: ATEX II 1G Ex ia IIC T4 Ga (-20°C		



Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

<= Ta <= +65OC) BASEEFA04ATEX0384; IECEx

BAS05.0039. Flammable: ATEX II 2G Ex ia d IIC

T4 Gb (-20°C <= Ta <= +65OC)

BASEEFA04ATEX0383; IECEx BAS05.0038.

CSA Class 1 Groups A

Approvals

С



ComastriDistribution

Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

Approvals



ComastriDistribution

Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

D Division 1



ComastriDistribution

Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

Allarme



ComastriDistribution

Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

95dB (multiple alarm options let you select

distinctive tones for different alarm levels), dual

colours red/blue flashing LEDs in a gas hazard,

internal vibration



ComastriDistribution

Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

Allarme



Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

95dB (più opzioni di allarme consentono di

selezionare toni distintivi per diversi livelli di

allarme)



ComastriDistribution

Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

Allarme



ComastriDistribution

Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

LED bicolore rosso / blu lampeggianti in caso di

pericolo di gas



ComastriDistribution

Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

Allarme



ComastriDistribution

Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

vibrazioni interne



ComastriDistribution

Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

Classificazione IP



ComastriDistribution

Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

IP65** (heavy rain)



ComastriDistribution

Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

Sampling



ComastriDistribution

Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

Optional manual aspirator



ComastriDistribution

Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

Sampling



ComastriDistribution

Phone: +390513510702 Mail: info@comastridistribution.com



Go to product

Optional manual aspirator