

ComastriDistribution

Phone: +390513510702

Mail: info@comastridistribution.com



Go to product



RSL200 - Powders and granulates vibrating level switches

0060

Servicies

After sale servicies

Ordinary and extraordinary maintenance, installation, staff training, spare parts, calibration and calibration for measuring instruments.



ComastriDistribution

Phone: +390513510702

Mail: info@comastridistribution.com



Go to product

Product description

Summary: The RSL200 is a compact tuning fork level switch designed for precise monitoring of powder or granule products. It uses an electrically excited tuning fork to detect level changes, triggering an intervention command when needed.

This makes it especially effective where other sensors fail due to electrical capacitance variations or electrostatic charges. The device offers digital calibration, multiple alarm options, and SPDT relay output. It's robust with an IP66 protection rating and available in ATEX-certified versions, making it suitable for a wide range of applications.

Can be powered by either AC or DC.



ComastriDistribution

Phone: +390513510702

Mail: info@comastridistribution.com



Go to product

General Features

Weight	1,5 kg	Response time	1s o 4s
Temperature	From -40°C to +150°C	Allarme	Output status detection mode
Classificazione IP	IP66	Pressure	Max 25 bar
Output	Relè 250Vac 5A max	Process	1" 1/2 GAS in AISI316
Power consumption	Max. 0,5W (Vdc); max. 5 VA (Vac)	Density	Min 20g/dm3
Density	Min 20g/dm3		

Models and prices

Model ref.	Certification	Power supply	Price VAT escl.
RSL200A0F1A	None	85÷230Vac - 50Hz	326.70 €
RSL200A0F3A	None	24Vdc/Vac - 36Vac 50Hz	326.70 €
RSL200A2F1A	ATEX II 1/2D Ex ta/tb IIIC T 150°C	85÷230Vac - 50Hz	391.50 €
	Da/Db Tamb -20° ÷ +60° IP66		
RSL200A2F3A	ATEX II 1/2D Ex ta/tb IIIC T 150°C	24Vdc/Vac - 36Vac 50Hz	391.50 €
	Da/Db Tamb -20° ÷ +60° IP66		