

ComastriDistribution

Phone: +390513510702

Mail: info @ comastridistribution.com



Go to product



F250 - Recirculating cooler

0069

Servicies

After sale servicies

Ordinary and extraordinary maintenance, installation, staff training, spare parts, calibration and calibration for measuring instruments.



ComastriDistribution

Phone: +390513510702

Mail: info@comastridistribution.com



Go to product

Product description

Recirculating coolers: environmentally friendly and economical chilling

JULABO recirculating coolers can handle virtually any cooling requirements in laboratories or industrial environments. Their efficiency makes them an environmentally-friendly and economical alternative to cooling with tap water. Compact models from JULABO are ideal for placement on or underneath a laboratory bench.

F250 Recirculating Cooler

JULABO F models require very little space and have very low procurement costs. Recirculating coolers of the F Series are a great way to replace costly tap water and are ideal for basic cooling tasks.

Advantages

Environmentally-friendly operation with low energy consumption

Compact design

Splash-proof membrane keypad with LED temperature display

Straightforward filling and draining

Filling level indicator

May be used with water, water/glycol, JULABO Thermal G



ComastriDistribution

Phone: +390513510702

Mail: info@comastridistribution.com



Go to product

General Features

Dimensions	H:240 mm L:400 mm P:520 mm	Weight	27 kg
Range	Pump capacity: 15 l/min	Flow rate	Pump capacity flow pressure: 0,35 bar
Temperature	From -10°C to +40°C	Connection	M10x1
Capacity	Cooling capacity (Ethanol): 20/10/5/0/-5 °C -	Display	LED, resolution 0.1
	0.25/0.22/0.21/0.18/0.09 kW		
Stability	Temperature: ±0.05°C	Control system	PID
Volume	Refrigerant stage 1: 113g	Volume	Filling: 1,7-2,6 L
Volume	Filling: 1,7-2,6 L		