



www.imada.it

DTXS 5Nm - Screw cap torque tester

0073

Servicies

After sale servicies

Ordinary and extraordinary maintenance, installation, staff training, spare parts, calibration and calibration for measuring instruments.

The prices could be not always up to date and they don't take into account any promotional sale on the e-commerce.



Product description

The Imada DTX series digital torque transducers are excellent bench-mounted instruments for torque measurement, easy to use, with high acquisition speed (2kHz), high sensitivity and excellent precision. Easily transportable, they can be used both in the laboratory but also in the production line. If installed on the MTS series of stands, they can form an economic torque control system with motorized speed control, ideal for guaranteeing uniformity of results even with different operators and the possibility of performing durability tests that are impossible to achieve by hand.

Standard Features

- OEL display visible even in the dark
- Multilingual settings menu in Italian
- 2000 Hz sampling rate
- Reading values in real time or peak mode
- Thrust ball bearing under the plate
- Accomodate specimens with dia. from 7 to 160mm
- With capacity max. up to 10Nm

- Resistance to overload up to 200% f.s.
- Internal memory records up to 1000 values
- It transmits data to the PC via USB
- USB, RS-232C, Digimatic and Analog outputs
- Limits with acoustic warnings and warning lights
- Digital comparator -NG / OK / + NG
- Internal rechargeable NiMh battery

?

Design

Characterized by a minimal design, these new torque meters have been redesigned to offer solidity and manageability. Made with a robust casing in die-cast aluminum and painted in fire, they are resistant to impacts and impermeable, with the upper shaped body for the collection of liquids. Under the bottle loading plate, flush with the hole, a thrust ball bearing neutralizes the possible pushing force of the operator, isolating the torque transducer below which remains sensitive to the rotation that occurs "on the horizontal plane".

Memory and data outputs

Internal non-volatile memory, with the possibility of recording up to 1000 numeric values that can be recalled on the display or with data transmission on a PC or a Mitutoyo printer with report. The instrument is supplied as standard with USB data outputs, RS232C, Mitutoyo digimatic, 2 VDC analog output (D / A), 3-threshold comparator (-NG / OK / + NG). The advanced DTXA model also allows the connection of a USB pendrive for recording measurements directly inside (the sampling frequency is selectable: 100Hz, 50Hz or 1Hz).

Tare and overload protection

The instrument allows the values to be reset by pressing a key (up to 10% of the flow) and automatic zeroing at adjustable intervals (from 1 to 25 seconds). It is also designed with an overload resistance of up to 200% of full scale without damage. The instrument flashes with a special LED light of over 110% of the flow and, if connected to the MTS series, in case of overload it sends a stop signal to the stand.



Display and functions

A large electroluminescent digital display also visible in the dark shows the reading of the values in real time or the still image on the maximum value reached, if the peak function is set. The display can be customized at the discretion of the operator who can choose which functions to display at the top and bottom of the screen. The high sampling rate and data acquisition rate (2000 data / sec) allows very rapid measurements to be measured with great accuracy. The display is updated 16 times per second and can indicate the direction of the vector, the unit of measurement, the function of recording the peak (1st and 2nd in the DTXA), the value of the angle (if the DTXA is connected with an MTS Imada stand), battery status, as well as date and time. A robust and simple membrane keyboard allows you to set and adjust all the functions of the instrument such as the tare, the unit of measure, the control limits, the memorization of a value, the activation of the peak recording function, data transmission, sampling filter, acoustic warnings, etc...

Handles, anchor holes, plates and pins

The compact dimensions and the grab handles it is equipped with make it extremely manageable and easy to transport, for use on multiple production lines. The handles are removable and the four holes allow you to firmly anchor the chassis on a table to perform tests with the stable instrument.

The torque transducers are equipped as standard with a standard aluminum plate to test specimens with Ø shapes ranging from 20 ~ 160mm. The fixing pins are easily adjustable to adapt to any particular. The plate is equipped with rail guides with holes to insert the support pins in different positions. The movement of the rails to block the sample is by screw tightening with a monopole. On request are available pins with increased height, to block specimens that require a firmer grip. As an alternative to the standard plate it is possible to order the reduced version of the plate, model DT-ST, ideal for housing small specimens such as vials (Ø 7 ~ 50mm).

Free ZT-Logger software

Free software to download data to your PC. Through the USB connection, the software transfers 10 data per second. to the PC allowing to save them in a CSV format. Furthermore, all internal memories of a dynamometer can be recalled on the PC at once and the corresponding statistical values can be calculated. Measurement efficiency can be improved by setting the dynamometer functions directly from the computer.

What's included

AC adapter, Inspection certificate, driver CD (includes simple data acquisition software), USB cable, L-key.



ComastriDistribution
Prodotti e soluzioni per l'industria S.r.l

26/04/2024

ComastriDistribution

Phone: +390513510702

Mail: info@comastridistribution.com



[Go to product](#)

General Features

Weight	4,5 kg	Accuracy	$\pm 5\% + 1$ digit
Battery life	Up to 8 hours of battery life, the message BATT flashes on the display when the charge is low	Data logging	2kHz sampling rate (2000 readings per second)
Temperature	From 0°C to +40°C	Connettività	USB and ± 2 V DC analog output
Power	Via 230V power supply	Sampling	2kHz sampling rate (2000 readings per second)
Measurements Units	N-m, N-cm, kgf-m, kgf-cm, lbf-in, ozf-in	Memory	Internal non-volatile memory, with the possibility of recording up to 1000 numeric values that can be recalled on the display or with data transmission on a PC via USB or Mitutoyo printer
Humidity	20-80% RH	Display	4-digit OLED digital display, membrane keypad with push-button sounder, polycarbonate display protection glass
Display	4-digit OLED digital display, membrane keypad with push-button sounder, polycarbonate display protection glass		

Base price:	VAT excluded	VAT included
	-	-

Model ref. DTXS-5N

The prices could be not always up to date and they don't take into account any promotional sale on the e-commerce.

comastridistribution.com

Page 4/4