



Comastri Distribution
Prodotti e soluzioni per l'industria S.r.l

29/03/2024

ComastriDistribution

Phone: +390513510702

Mail: info@comastridistribution.com




[Go to product](#)



RM3545 - Bench-top 5 digits milliohmeter

0080



Services

After sale services

Ordinary and extraordinary maintenance, installation, staff training, spare parts, calibration and calibration for measuring instruments.

The prices could be not always up to date and they don't take into account any promotional sale on the e-commerce.

comastridistribution.com

Page 1/3



Product description

The RM3544 milliohmeter is ideal for testing and trial on production lines and for quality control: it is typically used on windings, resistors, transformers, motors, etc., both on test benches and for quality control in production.

It covers a wide spectrum of resistance values: 9 measurement ranges from 30m Ω to 3M Ω . Measurement range from 1 Ω to 3.5 M Ω . 21msec response speed. "Scaling" function to convert the measured resistance value into other physical quantities such as, for example, the length of a cable. Ability to save and recall up to 10 different test configurations. Programmable comparator

The 5-digit benchtop milliohmeter has a wide power supply range of 90V to 264V 50/60 Hz.

High performance, 5 digits, 0,02% accuracy, 1 $\mu\Omega$ resolution, max measurable current: 300mA.

Simplifying high-accuracy resistance measurement

Guaranteed accuracy with no warm-up or zero setting

Convenient wide range options (measure from 0.000m Ω to 3.500M Ω , max. resolution 1 $\mu\Omega$)

High durability probes

Temperature correction

Easy-to-use resistance meter

High-intuitive advanced functionality

Footprint of just 215x166 mm

Ability to extend measurement cable length

High-speed, comprehensive productivity support

What's included

RM-3544

Power Cord

Clip type lead L2101

Instruction manual

Spare fuse

Warranty

A warranty of the duration of 1 year is provided.



General Features

Dimensions	H:215 mm L:80 mm P:166 mm	Weight	0,92kg
Temperature	From 0°C to +40°C	Power	Rated supply voltage: 100 to 240 VAC. Rated supply frequency: 50/60Hz
Humidity	<80%	Speed	FAST/MED/SLOW
Control system	Panel save parameter: resistance measurement ranges, measurement speed, comparator, ecc...	Functions	Temperature correction, comparator (ABS/REF%) key-lock, display digit count selection function, automatic power supply frequency setting, scaling, auto-hold
Measurements	Temperature (thermistor): from -10.0°C to 99,9°C	Measurements	Resistance: from 0.0000m? (30m? range) to 3.500M? (30M? range), 9ranges
Measurement method	4-terminal direct current (constant current), banana plug	Measurement method	4-terminal direct current (constant current), banana plug

Base price:	VAT excluded	VAT included
	-	-

Model ref. RM3544